Black Swan Manufacturing Co. 4540 W. Thomas Street Chicago, IL 60651-3318 1-800-252-5796

Fax: 1-773-227-3705

#### **Black Swan Store**

Home >> Products >> Cat 6 - Boiler and Heating System Compounds

search... Click to Search

#### Main Menu

#### Home

- Letter From The President
- Mission
   Statement and
   Philosophy
- History
- Corporate Information
- Certificate of Insurance
- Shipping Locations
- Manufacturers' Representatives
- Shipping Hazardous Materials
- What's New
- Barter
- Name Your Price
- In Conclusion



### Products

- Products
- GHS Safety Data Sheets
- List Price Sheets
- Product Line Drawings
- Solvent Cement Information

# Liquid Boiler Cleaner

Products - Cat 6 - Boiler and Heating System Compounds



## **DESCRIPTION**

**Black Swan Liquid Boiler Cleaner** is a powerful liquid designed to clean hot water systems. Removes scale, rust, grease, dirt and oil. **Liquid Boiler Cleaner** contains an inhibitor which will prevent rust and corrosion. It also stops priming and surging.

**Liquid Boiler Cleaner** is safe and easy to use. No need to drain or flush the system unless there are unusually dirty conditions. By using **Liquid Boiler Cleaner** you will save energy and promote maximum boiler efficiency.

## **DIRECTIONS**

## For Moderately Dirty Systems:

- 1. Pour **Liquid Boiler Cleaner** into boiler through safety valve or any other convenient opening.
- 2. To determine quantity of product to introduce into system, see chart below.
- Under normal circumstances no draining or flushing of the system is necessary.

## For Oily, Surging or Rusty Systems:

- Pour Liquid Boiler Cleaner into system per instructions above and allow to remain inn boiler for two weeks.
- 2. Allow water to cool and drain boiler.
- 3. Clean all parts of system thoroughly.



- 4. Fill the boiler with clean water and add a second dose of Black Swan **Liquid Boiler Cleaner** to system.
- 5. No draining or flushing of system is necessary.
- 6. For best results clean boiler once a year.

## **RECOMMENDED QUANTITIES**

E. D. R. Boiler Rating	Amt. For Cleaning	Amt. For Treating	Total Amt.
up to 600 sq. ft.	1 qt.	1 qt.	2 qt.
900 sq. ft.	2 qt.	2 qt.	4 qt.
1200 sq. ft.	4 qt.	4 qt.	8 qt.
1500 sq. ft.	6 qt.	6 qt.	12 qt.
1800 sq. ft.	8 qt.	8 qt.	16 qt.
2100 sq. ft.	10 qt.	10 qt.	20 qt.

### NOTE

For every 500 sq. ft. above 2100 sq. ft. add 2 quarts for cleaning and treating. The above amounts are based upon one quart treating 40 gallons of boiler water. For boilers having smaller water capacity use proportionately.

### **CAUTION**

Like

Do not take internally. Avoid contact with eyes. In case of eye contact, flush liberally with water. Call Physician.

## **UPC NUMBER AND CARTON INFORMATION**

STOCK NO.	SIZE	UPC NUMBER	CARTON CUBIC FEET	
06010	qt.	0 54647 06010 1	.649	
06012	gal.	0 54647 06012 5	1.380	
GHS Safety Data Sheet				
Buy Now				

Powered by Joomla!. valid XHTML and CSS.