



Click anywhere in the top half of this page for online articles about building interiors and interior drywall inspection, diagnosis, installation, and repair at InspectAPedia.com

SECTION 1
CHEMICAL PRODUCT AND IDENTIFICATION

| | | |
|--|--|---|
| United States Gypsum Company 550 West Adams Street Chicago, Illinois 60661-3637 A Subsidiary of USG Corporation | | Product Safety: 1 (800) 507-8899 www.usg.com Version Date: January 1, 2008 Version: 2 |
| PRODUCT(S) | All FIBEROCK® Brand | |
| CHEMICAL FAMILY / GENERAL CATEGORY | Wallboard, FIBEROCK | |
| SYNONYMS | Fiber-Reinforced Gypsum Panels Product | |

SECTION 2
HAZARD IDENTIFICATION

| | |
|--|---|
| EMERGENCY OVERVIEW: ΔWARNING! This product is not expected to produce any unusual hazards during normal use. Exposure to high dust levels may irritate the skin, eyes, nose, throat, or upper respiratory tract. | |
| POTENTIAL HEALTH EFFECTS (See Section 11 for more information) | |
| ACUTE : | |
| Inhalation | Exposure to dust generated during the handling or use of the product may irritate eyes, skin, nose, throat, and upper respiratory tract. Persons subjected to large amounts of this dust will be forced to leave area because of nuisance conditions such as coughing, sneezing and nasal irritation. Labored breathing may occur after excessive inhalation. If respiratory symptoms persist, consult physician. |
| Eyes | Dust can cause mechanical irritation of eyes. If burning, redness, itching, pain or other symptoms persist or develop, consult physician. |
| Skin | None known. |
| Ingestion | None known. |
| CHRONIC: | |
| Inhalation | The concentration of respirable crystalline silica measured in bulk samples of USG gypsum was less than 0.1 Wt.%. Industrial hygiene testing, following the NIOSH Method 7500, did not detect respirable crystalline silica in dust created during the cutting of USG gypsum wallboard panels by both the recommended score and snap technique and with the use of a power saw in a 10ft by 10ft room. Panels do not release respirable dust in their installed state and therefore do not present any known health hazards when installed and properly maintained. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. The risk of developing silicosis is dependent upon the exposure intensity and duration. |
| Eyes | None known. |
| Skin | None known. |

Click anywhere in the top half of this page for online articles about building interiors and interior drywall inspection, diagnosis, installation, and repair at InspectAPedia.com

| | |
|-----------|-------------|
| Ingestion | None known. |
|-----------|-------------|

TARGET ORGANS: Eyes, skin and respiratory system.

PRIMARY ROUTES OF ENTRY: Inhalation, eyes and skin contact.

CARCINOGENICITY CLASSIFICATION OF INGREDIENT(S) All substances listed are associated with the nature of the raw materials used in the manufacture of this product and are not independent components of the product formulation. All substances, if present, are at levels well below regulatory limits. See Section 11: Toxicology Information for detailed information.

| MATERIAL | IARC | NTP | ACGIH | CAL- 65 |
|-----------------------------------|------|------------|-------|------------|
| Vinyl Acetate Monomer | 2B | Not Listed | A3 | Not Listed |
| Acetaldehyde | 2B | 2 | A3 | Listed |
| Formaldehyde | 1 | 2 | A2 | Listed |
| Fibrous Glass-Scrim Reinforcement | 3 | 2 | A3 | Not Listed |
| Crystalline silica | 1 | 1 | A2 | Listed |

IARC - International Agency for Research on Cancer: 1- Carcinogenic to humans; 2A – Probably carcinogenic to humans; 2B – Possibly carcinogenic to humans; 3 - Not classifiable as a carcinogen; 4 – Probably not a carcinogen

NTP – National Toxicology Program (Health and Human Services Dept., Public Health Service, NIH/NIEHS): 1- Known to be carcinogen; 2- Anticipated to be carcinogens

ACGIH – American Conference of Governmental Industrial Hygienists: A1 – Confirmed human carcinogen; A2 – Suspected human carcinogen; A3 – Animal carcinogen; A4 - Not classifiable as a carcinogen; A5 – Not suspected as a human carcinogen

CAL-65 – California Proposition 65 “Chemicals known to the State of California to Cause Cancer”

Respirable crystalline silica: IARC: Group 1 carcinogen, NTP: Known human carcinogen. The weight percent of crystalline silica given represents total quartz and not the respirable fraction. The weight percent of respirable silica has not been measured in this product.

POTENTIAL ENVIRONMENTAL EFFECTS: This product has no known adverse effect on ecology. (See Section 12 for more information.)

SECTION 3 COMPOSITION, INFORMATION ON INGREDIENTS

| MATERIAL | WT% | CAS # |
|-------------------------------------|-----|-------------|
| Gypsum (CaSO4•2H2O) | >55 | 13397-24-5 |
| Cellulose | <20 | 9004-34-6 |
| Expanded Perlite | >10 | 93763-70-3 |
| Vinyl Acetate Acrylic Copolymer | <5 | Proprietary |
| Fibrous Glass - Scrim Reinforcement | <5 | 65997-17-3 |
| Polyhydrogenmethylsiloxane | <1 | 63148-57-2 |
| Crystalline Silica | <5 | 14808-60-7 |

All ingredients of this product are included in the U.S. Environmental Protection Agency's Toxic Substances Control Act Chemical Substance Inventory and the Canadian Domestic Substances List (DSL).

The weight percent for silica represents total quartz and not the respirable fraction.

SECTION 4 FIRST AID MEASURES



FIRST AID PROCEDURES

| | |
|------------|--|
| Inhalation | Remove to fresh air. Leave the area of exposure and remain away until coughing and other symptoms subside. Other measures are usually not necessary, however if conditions warrant, contact physician. |
| Eyes | In case of contact, do not rub or scratch your eyes. To prevent mechanical irritation, flush thoroughly with water for 15 minutes. If irritation persists, consult physician. |
| Skin | Wash with mild soap and water. If irritation persists, consult physician. |
| Ingestion | This product is not intended to be ingested or eaten. If gastric disturbance occurs, call physician. |

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED: Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema and asthma. Pre-existing skin diseases such as, but not limited to, rashes and dermatitis.

NOTES TO PHYSICIAN: Treatment should be directed at the control of symptoms and the clinical condition.

**SECTION 5
FIRE FIGHTING MEASURES**

| | | | |
|---|--|------------------------------------|----------------|
| General Fire Hazards | None known | | |
| Extinguishing Media | Water or use extinguishing media appropriate for surrounding fire. | | |
| Special Fire Fighting Procedures | Wear appropriate personal protective equipment. See section 8. | | |
| Unusual Fire/ Explosion Hazards | None known | | |
| Hazardous Combustion Products | None known | | |
| Flash Point | Not Determined | Auto Ignition | Not Applicable |
| Method Used | Not Applicable | Flammability Classification | Not Applicable |
| Upper Flammable Limit (UFL) | Not Determined | Rate of Burning | Not Applicable |
| Lower Flammable Limit (LFL) | Not Determined | | |

**SECTION 6
ACCIDENTAL RELEASE MEASURES**

CONTAINMENT: Collect panels from spillage and if not damaged or contaminated by foreign material, panels may be reclaimed.

CLEAN-UP: Use normal clean up procedures. No special precautions.

DISPOSAL: Follow all local, state, provincial and federal regulations. Never discharge large releases directly into sewers or surface waters.

**SECTION 7
HANDLING AND STORAGE**

Click anywhere in the top half of this page for online articles about building interiors and interior drywall inspection, diagnosis, installation, and repair at InspectAPedia.com

HANDLING: Avoid dust contact with eyes. Wear the appropriate eye protection against dust (See Section 8). Minimize dust generation and accumulation. Avoid breathing dust. Wear the appropriate respiratory protection against dust in poorly ventilated areas and if TLV is exceeded (see Sections 2 and 8). Use good safety and industrial hygiene practices. When moving board with a forklift or similar equipment, it is essential that the equipment be rated capable of handling the loads. The forks should always be long enough to extend completely through the width of the load. Fork spacing between supports should be one half the length of the panels or base being handled so that a maximum of 4' extends beyond the supports on either end.

Follow traditional building practices; such as management of water away from the interior of the structure to avoid the growth of mold, mildew and fungus. Remove any building products suspected of being exposed to sustained moisture and considered conducive to mold growth from the jobsite.

Gypsum panels are very heavy awkward loads posing the risk of severe back injury. Use proper lifting techniques.

STORAGE: Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities (see Section 10). Protect product from physical damage.

Protect from weather and prevent exposure to sustained moisture.

Gypsum Association literature recommends storing board flat to avoid damaging edges, warping the board and the potential safety hazards of the board falling over. However, in other situations, storing the board flat may cause a tripping hazard or exceed floor limit loads. If stacking board vertically, leave at least 4 inches from the wall to decrease the risk of falling board and no more than 6 inches to avoid too much lateral weight against the wall.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| MATERIAL | WT% | TLV (mg/m ³) | PEL(mg/m ³) |
|---|-----|--------------------------|--------------------------|
| Gypsum (CaSO ₄ •2H ₂ O) | >55 | 10 | 15 (T) / 5 (R) |
| Cellulose | <20 | 10 | 15 (T) / 5 (R) |
| Expanded Perlite | >10 | 10 | 15 (T) / 5 (R) |
| Vinyl Acetate Acrylic Copolymer | <5 | (NE) | (NE) |
| Fibrous Glass - Scrim Reinforcement | <5 | 1 f/cc (R) * | 15 (T) / 5 (R) |
| Polyhydrogenmethylsiloxane | <1 | (NE) | (NE) |
| Crystalline Silica | <5 | 0.025 (R) | 0.1 (R) |

(T)—Total; (R)—Respirable; (NE)—Not Established; (C)—Ceiling; (STEL)—Short-term exposure limit

(F)—Fume; (Du)—Dust; (M)—Mist

ppm—part per million; f/cc—fiber per cubic centimeter; mppcf— million particles per cubic foot

*ACGIH: 1 fiber/cubic centimeter air for fibers longer than 5 micrometers and thinner than 3 micrometers.

ENGINEERING CONTROLS: Provide ventilation sufficient to control airborne dust levels. If user operations generate airborne dust, use ventilation to keep dust concentrations below permissible exposure limits. Where general ventilation is inadequate, use process enclosures, local exhaust ventilation, or other engineering controls to control dust levels below permissible exposure limits.

RESPIRATORY PROTECTION: Wear a NIOSH/MSHA-approved respirator equipped with particulate cartridges when dusty in poorly ventilated areas, and if TLV is exceeded. A respiratory program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. If engineering controls are not possible, wear a properly fitted NIOSH/MSHA-approved particulate respirator.

OTHER PERSONAL PROTECTIVE EQUIPMENT:

| | |
|----------|--|
| Eye/Face | Wear eye protection, safety glasses or goggles, to avoid possible eye contact. |
|----------|--|



| | |
|---------|--|
| Skin | Wear gloves and protective clothing to prevent repeated or prolonged skin contact. |
| General | Selection of Personal Protective Equipment will depend on environmental working conditions and operations. |

**SECTION 9
PHYSICAL AND CHEMICAL PROPERTIES**

| | | | |
|------------------------------------|------------------------|--|--------------------------|
| Appearance | Off white to tan board | Vapor Density (Air = 1) | Not Applicable |
| Odor | Low to no odor | Specific Gravity (H₂O = 1) | 2.32 – 2.96 |
| Odor Threshold | Not Determined | Solubility in water (g/100g) | 0.26/100g |
| Physical State | Solid | Partition Coefficient | Not Applicable |
| pH @ 25 ° C | ~ 7 | Auto-ignition Temp | Not Determined |
| Melting Point | Not Applicable | Decomposition Temp | 2650°F/1450°C |
| Freezing Point | Not Applicable | Viscosity | Not Applicable |
| Boiling Point | Not Applicable | Particle Size | Not Applicable |
| Flash Point | Not Determined | Bulk Density | 54-62 lb/ft ³ |
| Evaporation Rate (BuAc = 1) | Not Applicable | Molecular Weight | ~ 172 |
| Upper Flammable Limit (UFL) | Not Determined | VOC Content | Zero |
| Lower Flammable Limit (LFL) | Not Determined | Percent Volatile | Zero |
| Vapor Pressure (mm Hg) | Not Applicable | | |

**SECTION 10
CHEMICAL STABILITY AND REACTIVITY**

| | |
|---------------------------------|---|
| STABILITY | Stable. |
| CONDITIONS TO AVOID | Contact with incompatibles (see below). |
| INCOMPATIBILITY | None known. |
| HAZARDOUS POLYMERIZATION | None known. |
| HAZARDOUS DECOMPOSITION | None known. |

**SECTION 11
TOXICOLOGICAL INFORMATION**

| |
|--|
| ACUTE EFFECTS: None known. |
| CHRONIC EFFECTS / CARCINOGENICITY: The concentration of respirable crystalline silica measured in bulk samples of USG gypsum was less than 0.1 Wt.%. Industrial hygiene testing, following the NIOSH Method 7500, did not detect respirable crystalline silica in dust created during the cutting of USG gypsum wallboard panels by both the recommended score and snap technique and with the |

Click anywhere in the top half of this page for online articles about building interiors and interior drywall inspection, diagnosis, installation, and repair at InspectAPedia.com

use of a power saw in a 10ft by 10ft room.

Panels do not release respirable dust in their installed state and therefore do not present any known health hazards when installed and properly maintained.

Crystalline Silica: Exposures to respirable crystalline silica are not expected during the normal use of this product; however, actual levels must be determined by workplace hygiene testing. The weight percent of respirable crystalline silica may not have been measured in this product. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. The risk of developing silicosis is dependent upon the exposure intensity and duration.

In June, 1997, IARC classified crystalline silica (quartz and cristobalite) as a human carcinogen. In making the overall evaluation, the IARC Working Group noted that carcinogenicity in humans was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs.

IARC states that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1).

SECTION 12 ECOLOGICAL INFORMATION

ENVIRONMENTAL TOXICITY: This product has no known adverse effect on ecology.

| | |
|--------------------------|-----------------|
| Ecotoxicity value | Not determined. |
|--------------------------|-----------------|

SECTION 13 DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of material in accordance with federal, state, and local regulations. Never discharge directly into sewers or surface waters. Consult with environmental regulatory agencies for guidance on acceptable disposal practices.

SECTION 14 TRANSPORT INFORMATION

U.S. DOT INFORMATION: Not a hazardous material per DOT shipping requirements. Not classified or regulated.

| | |
|----------------------|-----------------------|
| Shipping Name | Same as product name. |
|----------------------|-----------------------|

| | |
|---------------------|-----------------|
| Hazard Class | Not classified. |
|---------------------|-----------------|

| | |
|----------------|-----------------------|
| UN/NA # | None. Not classified. |
|----------------|-----------------------|

| | |
|----------------------|-------|
| Packing Group | None. |
|----------------------|-------|

| | |
|---------------------------|-----------------|
| Label (s) Required | Not applicable. |
|---------------------------|-----------------|

| | |
|------------------------|-----------------|
| GGVSec/MDG-Code | Not classified. |
|------------------------|-----------------|

| | |
|----------------------|-----------------|
| ICAO/IATA-DGR | Not applicable. |
|----------------------|-----------------|

| | |
|----------------|-------|
| RID/ADR | None. |
|----------------|-------|

| | |
|-------------|-------|
| ADNR | None. |
|-------------|-------|

**SECTION 15
REGULATORY INFORMATION**

UNITED STATES REGULATIONS

All ingredients of this product are included in the U.S. Environmental Protection Agency's Toxic Substances Control Act Chemical Substance Inventory.

| MATERIAL | WT% | 3 0 2 | 3 0 4 | 3 1 3 | CERCLA | CAA Sec. 112 | RCRA Code |
|---|-----|-------------|-------------|-------------|--------|-----------------|--------------|
| Gypsum (CaSO ₄ •2H ₂ O) | >55 | NL | NL | NL | NL | NL | NL |
| Cellulose | <20 | NL | NL | NL | NL | NL | NL |
| Expanded Perlite | >10 | NL | NL | NL | NL | NL | NL |
| Vinyl Acetate Acrylic Copolymer | <5 | NL | NL | NL | NL | NL | NL |
| Fibrous Glass - Scrim Reinforcement | <5 | NL | NL | NL | NL | NL | NL |
| Polyhydrogenmethylsiloxane | <1 | NL | NL | NL | NL | NL | NL |
| Crystalline Silica | <5 | NL | NL | NL | NL | NL | NL |

Key : NL = Not Listed

SARA Title III Section 302 (EPCRA) Extremely Hazardous Substances: Threshold Planning Quantity (TPQ)

SARA Title III Section 304 (EPCRA) Extremely Hazardous Substances: Reportable Quantity (RQ)

SARA Title III Section 313 (EPCRA) Toxic Chemicals: X= Subject to reporting under section 313

CERCLA Hazardous Substances: Reportable Quantity (RQ)

CAA Section 112 (r) Regulated Chemicals for Accidental Release Prevention: Threshold Quantities(TQ)

RCRA Hazardous Waste: RCRA hazardous waste code

CANADIAN REGULATIONS

This product has been classified in accordance with the hazard criteria of Controlled Product regulations and the MSDS contains all the information required by the Controlled Products Regulations. All ingredients of this product are included in the Canadian Domestic Substances List (DSL).

| MATERIAL | WT% | IDL Item # | WHMIS Classification |
|---|-----|------------|-------------------------|
| Gypsum (CaSO ₄ •2H ₂ O) | >55 | Not Listed | Not Listed |
| Cellulose | <20 | Not Listed | Not Listed |
| Expanded Perlite | >10 | Not Listed | D2A |
| Vinyl Acetate Acrylic Copolymer | <5 | Not Listed | Not Listed |
| Fibrous Glass - Scrim Reinforcement | <5 | Not Listed | Not Listed |
| Polyhydrogenmethylsiloxane | <1 | Not Listed | Not Listed |
| Crystalline Silica | <5 | 1406 | D2A |

IDL Item#: Canadian Hazardous Products Act – Ingredient Disclosure List Item #

WHMIS Classification: Workplace Hazardous Material Information System

Risk and Safety Phrases defined by European Union Directive 67/548/EEC (Annex III and IV)

R-Phrase(s): R36/37/38

S-Phrase(s): S51 S38 S39 S2


**SECTION 16
 OTHER INFORMATION**

Label Information

Δ WARNING!

Dust may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Avoid irritation by reducing exposure to dust. Use in a well-ventilated area or provide sufficient local ventilation. If dusty, wear a NIOSH/MSHA-approved dust respirator. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If irritation persists, call physician. Wash with soap and water after use. Do not ingest. If ingested, call physician. If cutting board with a power tool, use a wet or vacuum saw to reduce the amount of dust generated. Panels are heavy and can fall over, causing serious injury or death. Avoid creating a tripping hazard and do not exceed floor limit loads. Product safety information: (800) 507-8899 or www.usg.com.
 KEEP OUT OF REACH OF CHILDREN.

INFORMATION FOR HANDLING AND IDENTIFICATION OF CHEMICAL HAZARDS

| | | | | | | | | | | | | | | | | | | |
|---------------------|---|--|---------------|---------------------|--|--------|---|---|--------------|--|---|-----------------|--|---|---------------------|--|---|--------------------|
| NFPA Ratings: | |  | HIMS Ratings: | | <table border="1"> <tr> <td>HEALTH</td> <td>*</td> <td>1</td> </tr> <tr> <td>FLAMMABILITY</td> <td></td> <td>0</td> </tr> <tr> <td>PHYSICAL HAZARD</td> <td></td> <td>0</td> </tr> <tr> <td>PERSONAL PROTECTION</td> <td></td> <td>E</td> </tr> </table> | HEALTH | * | 1 | FLAMMABILITY | | 0 | PHYSICAL HAZARD | | 0 | PERSONAL PROTECTION | | E | 0 = Minimal Hazard |
| HEALTH | * | | 1 | | | | | | | | | | | | | | | |
| FLAMMABILITY | | | 0 | | | | | | | | | | | | | | | |
| PHYSICAL HAZARD | | | 0 | | | | | | | | | | | | | | | |
| PERSONAL PROTECTION | | E | | | | | | | | | | | | | | | | |
| Health: | 1 | Health: | 1 | 1 = Slight Hazard | | | | | | | | | | | | | | |
| Fire: | 0 | Fire: | 0 | 2 = Moderate Hazard | | | | | | | | | | | | | | |
| Reactivity: | 0 | Reactivity: | 0 | 3 = Serious Hazard | | | | | | | | | | | | | | |
| | | | | | 4 = Severe Hazard | | | | | | | | | | | | | |

E – Safety glasses, gloves and dust respirator

Key/Legend

| | |
|-------|---|
| TLV | Threshold Limit Value |
| PEL | Permissible Exposure Limit |
| CAS | Chemical Abstracts Service (Registry Number) |
| NIOSH | National Institute for Occupational Safety and Health |
| MSHA | Mine Safety and Health Administration |
| OSHA | Occupational Health and Safety Administration |
| ACGIH | American Conference of Governmental Industrial Hygienists |
| IARC | International Agency for Research on Cancer |
| DOT | United States Department of Transportation |
| EPA | United States Environmental Protection Agency |
| NFPA | National Fire Protection Association |
| HMIS | Hazardous Materials Identification System |
| PPE | Personal Protection Equipment |
| TSCA | Toxic Substances Control Act |
| DSL | Canadian Domestic Substances List |
| NDSL | Canadian Non-Domestic Substances List |
| SARA | Superfund Amendments and Reauthorization Act of 1986 |
| CAA | Clean Air Act |



MATERIAL SAFETY DATA SHEET

All FIBEROCK® Brand

MSDS #54-CGC-FIB

Page 9 of 9

| | |
|--|--|
| EPCRA | Emergency Planning & Community Right-to-know Act |
| RCRA | Resource Conservation and Recovery Act |
| CERCLA | Comprehensive Environmental Response, Compensation and Liability Act of 1980 |
| UN/NA# | United Nations/North America number |
| CFR | Code of Federal Regulations |
| WHMIS | Workplace Hazardous Material Information System |
| | |
| Prepared by: Product Safety USG Corporation 550 West Adams Street Chicago, IL 60661-3637 | |
| The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for his/her own particular use. | |
| END | |

Click anywhere in the top half of this page for online articles about building interiors and interior drywall inspection, diagnosis, installation, and repair at InspectAPedia.com
InspectAPedia.com is an independent online encyclopedia and has no relationship, business or otherwise, with the provider of this MSDS information.