




EcoFlush is Ecologic and Economic!

EcoFlush is perfect for septic tanks or when you need to save water! You can install it to either a traditional sewage system or to your own individual septic tank. It fits a regular 110 outlet, and you can choose to have separate or combined outlet. For combined outlet, make sure to have an adapter for the urine hose. (see image).

0,3 Liter

The small flush uses about 0,3 L. The water comes from the front och and flushes down the urine bowl and continues over the edge to the rest of the bowl for highest possible hygiene.




2,5 Liter


The big flush uses about 2,5 L.
The force of the water comes
from the back sides and the
front och rinses the entire
bowl.

Flush only where it's needed!


By using a urine separating WC you are able to use radically less water to flush! A person makes an average of 6 toilet visits a day. Since 5 of those contains only urine you are able to use the small flush most of the times. If using the small flush 5 of 6 times, the average flush volume is only 1 liter! That is 70-80% less than all common toilets on the market! EcoFlush flushing tecnique and built-in water trap is completely unique in the market!



Separate urine outlet



Combined outlet



Details

Water connection: Flexible stainless 1/2", R15 Flush volumes: Big flush: 2,5 L, Urine flush: 0,3 L

Average volumes / flush: approx 1 Liter. (if used correctly)

Urine piping: 50mm. 50 mm adapter is included.

Feaces Piping: Fits 110 mm.

Urine hose: 19mm white, included. (mounted) **Toilet seat:** Standard seat white plastic included.

RSK-nr EcoFlush: 7809023 RSK-nr Jafo-stos: 3106664

